



## H2 (High Speed) Direct Drive Aluminum Elevator

### Industrial Duty Integrated with a New Ultra Modern Appeal

- All Aluminum and Stainless Steel Construction
- Low Draft Design
- Very Modern Compact Drive Units
- Stainless Steel Equalizer Arms with Quad Upper Rollers
- Aluminum Bunks (Standard up to 20,000 lbs. if applicable)
- Stainless Steel Cables
- Adjustable Heavy Duty Guide Poles
- Piling or Seawall Mount
- Standard Angle is 25° (Available in Various Angles including Vertical)
- 15 Year Limited Warranty

### Options:

- SEArmor Corrosion Resistant Winders for Long Lasting Durability
- Wash Down Stainless “Hurricane” Motors
- Wireless Remote Control
- Auto Stop and Limit Switch
- Complete Disconnect Switch
- Stainless Steel Wash Down “Hurricane” Motors
- Underwater Bracing (for Deepwater Applications)
- Cable Retention System



## ⚡ Specifications ⚡

\*\*\*See our “Complete list of Other Accessories”

Size	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Track Size	Max. Beam	Cradle Dimensions	Bunks	Pile Size
5,000 lb.	(2) 1 HP	240V/20A	5/16” x 30’ Stainless Steel	12’	6” x 4” x 25’ I-Beam	8’ 0”	7’ Dual Forks	3” x 8” x 12’ Aluminum Bunks	8” Min.
7,000 lb.	(2) 1 1/2 HP	240V/25A	5/16” x 30’ Stainless Steel	12’	8” x 5” x 25’ I-Beam	8’ 0”	7’ Dual Forks	3” x 8” x 12’ Aluminum Bunks	8” Min.
10,000 lb.	(2) 2 HP	240V/25A	5/16” x 30’ Stainless Steel	12’	8” x 5” x 25’ I-Beam	9’ 0”	8’ Dual Forks	3” x 10” x 12’ Aluminum Bunks	10” Min.
12,000 lb.	(2) 2 HP	240V/30A	5/16” x 42’ Stainless Steel	11’	10” x 6” x 25’ I-Beam	10’ 0”	8’ Dual Forks	3” x 10” x 12’ Aluminum Bunks	10” Min.
14,000 lb.	(2) 2 HP	240V/30A	5/16” x 42’ Stainless Steel	11’	10” x 6” x 25’ I-Beam	10’ 0”	8’ Dual Forks	3” x 10” x 14’ Aluminum Bunks	10” Min.
15,000 lb.	(2) 2 HP	240V/30A	5/16” x 42’ Stainless Steel	11’	10” x 6” x 25’ I-Beam	10’ 0”	8’ Dual Forks	3” x 10” x 14’ Aluminum Bunks	10” Min.
17,000 lb.	(2) 2 HP	240V/30A	5/16” x 56’ Stainless Steel	11’	12” x 7” x 25’ I-Beam	10’ 0”	10’ Dual Forks	3” x 10” x 14’ Aluminum Bunks	12” Min.
20,000 lb.	(2) 2 HP	240V/30A	5/16” x 56’ Stainless Steel	11’	12” x 7” x 25’ I-Beam	12’ 6”	10’ Dual Forks	3” x 10” x 14’ Aluminum Bunks	12” Min.